

Series 08900/08500 Drum Faucets. Justrite self-closing **Safety Faucets** incorporate an internal flame arrester which prevents flashback of fire into the drum. Brass and stainless steel faucets feature a Polytetrafluoroethylene (PTFE)® seal. Adjustable models screw tightly into drum and can be adjusted to dispensing position, with spout downward, without thread damage or leakage. Faucet extensions provide extra dispensing accuracy and prevents spills.

For trouble-free dispensing of viscous noncorrosive flammables such as adhesives, paint or heavy oils above 2000 SSU (about 30W oil), use Justrite's 2" gate valves and/or .75" **Viscous Liquids Faucets**. Flame arresters are not provided on viscous liquid faucets.



Drum Faucets

Description	NPT (inch)	NPT (mm)	Approv./Lstg. Regulation	Ship Wt. Ctn. (Lbs)	Ship Wt. Ctn. (Kg)	Model No.
Brass control flow lab safety faucet	.75	19	FM	1	0.5	08540
Brass drum gate valve, viscous liquids	2	51	FM	6.8	3.1	08552
Flexible faucet extension, 6" (152mm) long, brass for use only with 08540	-	-	:	0.3	0.1	08584
Flexible faucet extension, 6" (152mm) long, stainless steel	-	-	:	0.3	0.1	08587
Brass safety faucet, rigid	.75	19	FM	1.3	0.6	08902
Brass safety faucet, adjustable	.75	19	FM	1.5	0.7	08910
Stainless steel safety faucet, adjustable	.75	19	FM	1.5	0.7	08916
Flexible faucet extension, 8" (203mm) long	-	-	:	0.3	0.1	08930
Flexible faucet extension, 3.25" (83mm) long, brass	-	-	:	0.2	0.1	08932
Brass faucet, viscous liquids	.75	19	FM	1.3	0.6	08955