

# Kromet 836 LC

## DESCRIPTION AND GENERAL PROPERTIES

- **Length (inches)** 10.6 - 12.6
- **Wrist** Knitted wrist
- **Colour/Color** Grey
- **Interior finish** Seamless textile support from HDPE fibres
- **Exterior finish** Leather layer on palm with reinforced thumb / index
- **Size / EAN** 7 8 9 10 11
- **Packaging** 1 pair/bag - 12 pairs/bag - 48 pairs/carton



## PERFORMANCE RESULTS

Certification category 2



X1XXXX



4543  
ISO 13997 :  
19.8 N (2019 g)

ISO 13997 defines the weight on the blade required to cut in a single movement.

Data was obtained according to ISO 13997, from the average of several measurements. As individual specimens will obviously have greater or lesser cut resistance than the average, so this result can provide only a general indication of the cut resistance of any protective material.

### Legends



**MECHANICAL HAZARDS**  
EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4

Abrasion resistance  
Blade cut resistance  
Tear resistance  
Puncture resistance



**LOW CHEMICAL PROTECTION**  
EN 374



**MICRO-ORGANISMS**  
EN 374



**RADIOACTIVE CONTAMINATION**  
EN 421



**SPECIFIC CHEMICAL PROTECTION**  
EN 374

Letter Code Chemical product

A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS**  
EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1

Convective cold resistance  
Contact cold resistance  
Water permeability



**HEAT AND FIRE**  
EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4

Burning behaviour  
Contact heat resistance  
Convective heat resistance  
Radiant heat resistant  
Resistance to small drops of molten metal  
Resistance to large quantities of molten metal

For more details: [www.mapa-pro.com](http://www.mapa-pro.com)

**MAPA**  
PROFESSIONAL

[www.mapa-pro.com](http://www.mapa-pro.com)

# Kromet 836 LC

## DESCRIPTION AND GENERAL PROPERTIES

- Excellent cut resistance on all parts of the glove
- Reinforced protection of the fore-arm thanks to its longer cuff
- Good resistance to wear and good puncture resistance (barbs) due to leather palm
- Reinforced crotch between thumb and forefinger.

## MAIN FIELDS OF USE

### Automotive/mechanical industry

- [Metal working](#)
- Handling untrimmed parts or sheet metal
- Handling sheet metal
- Handling parts post-press
- Cutting strips (plasma etc.)

## INSTRUCTIONS FOR USE

### Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- It is not recommended to use these gloves for persons sensitized to natural latex (wrist with elastic natural rubber)
- Put the gloves on dry, clean hands.
- Inspect the gloves for cracks or snags before reusing them.
- Not be used next to moving machinery.

### Storage conditions

- Store the glove in their original packaging protected from light, heat and humidity.

### Laundering conditions

- Wiping the dirty oily gloves with a dry cloth before taking off.
- Caution: inappropriate glove usage or cleaning may alter performance levels.
- Ensure the inside of the glove is dry before reusing them. Discard the glove if damaged.

### Drying conditions

- Ensure the inside of the gloves are dry before putting them on again.

### Food contact US

FDA 21CFR 177.2600

## LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH)

- CE-Type Examination Certificate

0075/014/162/01/15/0083

- Issued by the notified body nr

0075- CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France