

# UT520 SERIES Earth Ground Testers

# UNI-T®

UT521 / UT522



EN 61010-1  
EN 61010-2-030  
EN 61326-1



■ UT521



■ UT522

## SPECIFICATIONS



Specifications	Range	Best Accuracy	
Model		UT521	UT522
Earth Resistance (Ω)	0~20Ω	±(2%+10)	
	0~200Ω	±(2%+3)	
	0~2000Ω	±(2%+3)	
	0~40Ω		±(2%+20)
	0~400Ω		±(2%+3)
	0~4000Ω		±(2%+3)
AC Earth Voltage (V)	0~200V	±(1%+4)	
	0~400V		±(1%+6)
	Frequency:50Hz/60Hz	✓	✓
<b>Features</b>			
Display Count		2000	4000
Manual Range		✓	✓
Auto Power Off	Around 10 Minutes	✓	✓
Low Battery Indication		✓	✓
Data Hold		✓	✓
Data Storage		20	20
LCD Backlight		✓	✓
Full Icon Display		✓	✓
Double Insulation Protection		✓	✓
Contact Badness Display	Port C or Port E don't contact Display"----Ω"	✓	✓
Over-Range Display	Display "OL"	✓	✓
Simple 2-Wires Testing		✓	✓
Precision 3-Wires Testing		✓	✓

## GENERAL CHARACTERISTICS

Power	1.5V Batteries(LR6) × 6
LCD Size	70.6mm × 34mm
Product Color	Red and Gray
Product Net Weight	560 g
Product Size	160mm × 100mm × 70.5mm
Standard Accessories	Batteries, Carrying Bag, Test Lead, Simple Test Lead, Test Probe
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	8 PCs
Standard Carton Measurement	530mm × 300mm × 350mm (0.056 CBM Per Standard Carton)
Standard Carton Gross Weight	19.8 Kg